



SCREAMIN' DEMON

Features

- Available in 2 Different Heights: 30" & 46"
- 24 inches in Chamber Length
- 18 inches in Outside Diameter
- Fully Assembled with M 98 Zoeller 1/2 HP Sump Pump.
- 2 Solid Covers, Top Cover has Viewing Port
- 2 Grate Covers
- 9 Ft. Power Cord
- 1 1/2" (1.5") stubbed discharge for easy hookup.
- Includes FDM's Fully Adjustable Sump Pump Discharge Line Stub
- Holds 11.75 Gallons of Water



Optional : 250 Watt Heater

- Thermostatically controlled. This means it will automatically turn on and off as needed to keep the water from freezing.
- Tested & certified by MET Labs and exceeds USA/CA electrical safety standards.
- 12 foot power cord.
- 6" Round



Optional: 2 ft of Chamber with Split Coupler

Each chamber can hold an additional 11.75 gallons of water.



Pump Specifications

Horsepower: 1/2 HP

Voltage: 115 V

Phase: 1 Ph

Amps: 9.4

Hertz: 60 Hz

RPM: 1725

Discharge: 1-1/2" NPT

Solids Handling: 1/2" (12 mm) spherical solids

On/Off Points: 9-1/2" (24 cm) / 3" (8 cm)

Impeller Material: Engineered Plastic

Impeller Type: Vortex Impeller

Cord Length: 9' (2.7 m)

Max Head 23' (7 m)

Flows up to 72 GPM (273 LPM)

